

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 March 2005 (17.03.2005)


PCT

(10) International Publication Number
WO 2005/024932 A2

- (51) International Patent Classification⁷: **H01L 21/50**
- (21) International Application Number:
PCT/JP2004/013281
- (22) International Filing Date:
7 September 2004 (07.09.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-315269 8 September 2003 (08.09.2003) JP
- (71) Applicant (for all designated States except US): **MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD.**
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 5718501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KABESHITA, Akira. HAMASAKI, Kurayasu. MINAMITANI, Shozo. MAKINO, Yoichi. TANI, Noriyuki.**
- (74) Agents: **KAWAMIYA, Osamu et al.**; Aoyama & Partners, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 5400001 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: APPARATUS AND METHOD FOR REMOVING SEMICONDUCTOR CHIP AND APPARATUS FOR FEEDING SEMICONDUCTOR CHIPS



(57) Abstract: While a vicinity of a bottom surface-side region of a pressure-sensitive adhesive sheet (3) corresponding to an adhesion region (R1) of a semiconductor chip (1) are sucked and held, a plurality of protruding portions (30) of a removing member (21) are brought into contact with the bottom surface of the semiconductor chip through the adhesive sheet at the region. Also, the adhesive sheet is sucked in between the respective protruding portions so as to change a surface bonding of the semiconductor chip to the adhesive sheet by adhesion to a point bonding, and further the removing member is moved along the bottom surface of the semiconductor chip so as to change a position of the point bonding and decrease bonding force to the adhesive sheet by the adhesion. Then, the semiconductor chip is removed from the adhesive sheet.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.